



## PRODUCT SPECIFICATIONS

### Studding Outlets

Dimensions Are In Inches - Weights Are In Pounds

Class 150											
SIZE (BORE)	THICK	O.D.	RF O.D.	STUD CIRCLE	STUDS			TAP DEPTH	HOLE DEPTH	WEIGHT	
					NO.	SIZE	TPI			BASE	PER INCH
B	T	A	R	C	J	M	I	E	F	BASE	PER INCH
1/2	1.25	3.50	1.38	2.38	4	1/2	13	0.56	0.88	3.7	2.7
3/4	1.25	3.88	1.69	2.75	4	1/2	13	0.56	0.88	4.5	3.2
1	1.25	4.25	2.00	3.12	4	1/2	13	0.56	0.88	5.3	3.8
1 1/4	1.25	4.62	2.50	3.50	4	1/2	13	0.56	0.88	6.2	4.4
1 1/2	1.25	5.00	2.88	3.88	4	1/2	13	0.56	0.88	7.2	5.1
2	1.50	6.00	3.62	4.75	4	5/8	11	0.75	1.12	12	7.1
2 1/2	1.50	7.00	4.12	5.50	4	5/8	11	0.75	1.12	16	9.5
3	1.50	7.50	5.00	6.00	4	5/8	11	0.75	1.12	18	11
3 1/2	1.50	8.50	5.50	7.00	8	5/8	11	0.75	1.12	22	13
4	1.50	9.00	6.19	7.50	8	5/8	11	0.75	1.12	24	14
5	1.75	10.00	7.31	8.50	8	3/4	10	0.88	1.31	32	17
6	1.75	11.00	8.50	9.50	8	3/4	10	0.88	1.31	36	19
8	1.75	13.50	10.62	11.75	8	3/4	10	0.88	1.31	51	28
10	1.81	16.00	12.75	14.25	12	7/8	9	1.00	1.44	74	35
12	1.81	19.00	15.00	17.00	12	7/8	9	1.00	1.44	104	48
14	2.00	21.00	16.25	18.75	12	1	8	1.12	1.56	133	55
16	2.00	23.50	18.50	21.25	16	1	8	1.12	1.56	160	66
18	2.25	25.00	21.00	22.75	16	1 1/8	8	1.25	1.81	174	67
20	2.25	27.50	23.00	25.00	20	1 1/8	8	1.25	1.81	205	79
24	2.50	32.00	27.25	29.50	20	1 1/4	8	1.44	2.12	281	100

Class 300											
SIZE (BORE)	THICK	O.D.	RF O.D.	STUD CIRCLE	STUDS			TAP DEPTH	HOLE DEPTH	WEIGHT	
					NO.	SIZE	TPI			BASE	PER INCH
B	T	A	R	C	J	M	I	E	F	BASE	PER INCH
1/2	1.25	3.75	1.38	2.62	4	1/2	13	0.56	0.88	4.3	3.1
3/4	1.50	4.62	1.69	3.25	4	5/8	11	0.75	1.12	7.5	4.6
1	1.50	4.88	2.00	3.50	4	5/8	11	0.75	1.12	8.3	5.1
1 1/4	1.50	5.25	2.50	3.88	4	5/8	11	0.75	1.12	9.5	5.8
1 1/2	1.75	6.12	2.88	4.50	4	3/4	10	0.88	1.31	15	7.8
2	1.50	6.50	3.62	5.00	8	5/8	11	0.75	1.12	14	8.5
2 1/2	1.75	7.50	4.12	5.88	8	3/4	10	0.88	1.31	21	11
3	1.75	8.25	5.00	6.62	8	3/4	10	0.88	1.31	25	14
3 1/2	1.75	9.00	5.50	7.25	8	3/4	10	0.88	1.31	29	15
4	1.75	10.00	6.19	7.88	8	3/4	10	0.88	1.31	35	19
5	1.75	11.00	7.31	9.25	8	3/4	10	0.88	1.31	41	21
6	1.75	12.50	8.50	10.62	12	3/4	10	0.88	1.31	51	27
8	1.88	15.00	10.62	13.00	12	3/4	9	1.00	1.44	76	36
10	2.12	17.50	12.75	15.25	16	1	8	1.12	1.56	110	46
12	2.25	20.50	15.00	17.75	16	1 1/8	8	1.25	1.81	158	61
14	2.25	23.00	16.25	20.25	20	1 1/8	8	1.25	1.81	190	74
16	2.50	25.50	18.50	22.50	20	1 1/4	8	1.44	2.12	245	88
18	2.50	28.00	21.00	24.75	24	1 1/4	8	1.44	2.12	286	102
20	2.50	30.50	23.00	27.00	24	1 1/4	8	1.44	2.12	332	118
24	2.88	36.00	27.25	32.00	24	1 1/4	8	1.69	2.38	515	160