



Studding Outlets

Dimensions Are In Inches - Weights Are In Pounds

Class 600											
SIZE (BORE)	THICK	O.D.	RF O.D.	STUD CIRCLE	STUDS			TAP DEPTH	HOLE DEPTH	WEIGHT	
					NO.	SIZE	TPI			BASE	PER INCH
B	T	A	R	C	J	M	I	E	F	BASE	PER INCH
1/2	1.50	3.75	1.38	2.62	4	1/2	13	0.56	0.88	4.4	3.1
3/4	1.75	4.62	1.69	3.25	4	5/8	11	0.75	1.12	7.6	4.6
1	1.75	4.88	2.00	3.50	4	5/8	11	0.75	1.12	8.4	5.1
1 1/4	1.75	5.25	2.50	3.88	4	5/8	11	0.75	1.12	9.7	5.8
1 1/2	1.94	6.12	2.88	4.50	4	3/4	10	0.88	1.31	15	7.8
2	1.75	6.50	3.62	5.00	8	5/8	11	0.75	1.12	14	8.5
2 1/2	2.00	7.50	4.12	5.88	8	3/4	10	0.88	1.31	21	11
3	2.00	8.25	5.00	6.62	8	3/4	10	0.88	1.31	25	13
3 1/2	2.12	9.00	5.50	7.25	8	7/8	9	1.00	1.44	33	15
4	2.12	10.75	6.19	8.50	8	7/8	9	1.00	1.44	48	22
5	2.25	13.00	7.31	10.50	8	1	8	1.12	1.56	79	32
6	2.25	14.00	8.50	11.50	12	1	8	1.12	1.56	87	36
8	2.50	16.50	10.62	13.75	12	1 1/8	8	1.25	1.81	121	46
10	2.75	20.00	12.75	17.00	16	1 1/4	8	1.44	2.12	189	67
12	2.75	22.00	15.00	19.25	20	1 1/4	8	1.44	2.12	213	76
14	2.88	23.75	16.25	20.75	20	1 3/8	8	1.56	2.25	247	82
16	3.00	27.00	18.50	23.75	20	1 1/2	8	1.69	2.38	336	105
18	3.25	29.25	21.00	25.75	20	1 5/8	8	1.88	2.56	405	118
20	3.25	32.00	23.00	28.50	24	1 5/8	8	1.88	2.56	475	139
24	3.75	37.00	27.25	33.00	24	1 7/8	8	2.12	3.00	670	176

Class 900											
SIZE (BORE)	THICK	O.D.	RF O.D.	STUD CIRCLE	STUDS			TAP DEPTH	HOLE DEPTH	WEIGHT	
					NO.	SIZE	TPI			BASE	PER INCH
B	T	A	R	C	J	M	I	E	F	BASE	PER INCH
1/2	2.00	4.75	1.38	3.25	4	3/4	10	0.88	1.31	9.2	5.0
3/4	2.00	5.12	1.69	3.50	4	3/4	10	0.88	1.31	11	5.7
1	2.12	5.88	2.00	4.00	4	7/8	9	1.00	1.44	16	7.5
1 1/4	2.12	6.25	2.50	4.38	4	7/8	9	1.00	1.44	18	8.3
1 1/2	2.25	7.00	2.88	4.88	4	1	8	1.12	1.56	25	10
2	2.12	8.50	3.62	6.50	8	7/8	9	1.00	1.44	32	15
2 1/2	2.25	9.62	4.12	7.50	8	1	8	1.12	1.56	46	19
3	2.12	9.50	5.00	7.50	8	7/8	9	1.00	1.44	39	18
4	2.50	11.50	6.19	9.25	8	1 1/8	8	1.25	1.81	67	26
5	2.75	13.75	7.31	11.00	8	1 1/4	8	1.44	2.12	103	37
6	2.50	15.00	8.50	12.50	12	1 1/8	8	1.25	1.81	109	42
8	3.00	18.50	10.62	15.50	12	1 3/8	8	1.56	2.25	189	62
10	3.00	21.50	12.75	18.50	16	1 3/8	8	1.56	2.25	246	81
12	3.00	24.00	15.00	21.00	20	1 3/8	8	1.56	2.25	293	96
14	3.25	25.25	16.25	22.00	20	1 1/2	8	1.69	2.38	311	98
16	3.50	27.75	18.50	24.25	20	1 5/8	8	1.88	2.56	390	114
18	3.88	31.00	21.00	27.00	20	1 7/8	8	2.12	3.00	535	142
20	4.25	33.75	23.00	29.50	20	2	8	2.25	3.31	659	164
24	5.12	41.00	27.25	35.50	20	2 1/2	8	2.81	4.00	1189	246