



## PRODUCT SPECIFICATIONS

### Studding Outlets

Dimensions Are In Inches - Weights Are In Pounds

Class 1500												
SIZE (BORE)	THICK	O.D.	RF O.D.	STUD CIRCLE	STUDS			TAP DEPTH	HOLE DEPTH	WEIGHT		
					NO.	SIZE	TPI			BASE	PER INCH	
B	T	A	R	C	J	M	I	E	F	BASE	PER INCH	
1/2	2.00	4.75	1.38	3.25	4	3/4	10	0.88	1.31	9.2	5.0	
3/4	2.00	5.12	1.69	3.50	4	3/4	10	0.88	1.31	11	5.7	
1	2.12	5.88	2.00	4.00	4	7/8	9	1.00	1.44	16	7.5	
1 1/4	2.12	6.25	2.50	4.38	4	7/8	9	1.00	1.44	18	8.3	
1 1/2	2.25	7.00	2.88	4.88	4	1	8	1.12	1.56	25	10	
2	2.12	8.50	3.62	6.50	8	7/8	9	1.00	1.44	32	15	
2 1/2	2.25	9.62	4.12	7.50	8	1	8	1.12	1.56	46	19	
3	2.50	10.50	5.00	8.00	8	1 1/8	8	1.25	1.81	58	23	
4	2.75	12.25	6.19	9.50	8	1 1/4	8	1.44	2.12	83	30	
5	3.12	14.75	7.31	11.50	8	1 1/2	8	1.69	2.38	136	43	
6	3.00	15.50	8.50	12.50	12	1 3/8	8	1.56	2.25	136	45	
8	3.50	19.00	10.62	15.50	12	1 5/8	8	1.88	2.56	224	66	
10	3.88	23.00	12.75	19.00	12	1 7/8	8	2.12	3.00	363	95	
12	4.12	26.50	15.00	22.50	16	2	8	2.25	3.31	494	124	
14	4.25	29.50	16.25	25.00	16	2 1/4	8	2.56	3.56	652	150	
16	5.00	32.50	18.50	27.75	16	2 1/2	8	2.81	4.00	851	178	
18	5.50	36.00	21.00	30.50	16	2 3/4	8	3.12	4.38	1119	216	
20	5.88	38.75	23.00	32.75	16	3	8	3.44	4.62	1356	245	
24	6.75	46.00	27.25	39.00	16	3 1/2	8	4.00	5.38	2184	343	

Class 2500												
SIZE (BORE)	THICK	O.D.	RF O.D.	STUD CIRCLE	STUDS			TAP DEPTH	HOLE DEPTH	WEIGHT		
					NO.	SIZE	TPI			BASE	PER INCH	
B	T	A	R	C	J	M	I	E	F	BASE	PER INCH	
1/2	2.00	5.25	1.38	3.50	4	3/4	10	0.88	1.31	11	6.1	
3/4	2.00	5.50	1.69	3.75	4	3/4	10	0.88	1.31	12	6.6	
1	2.12	6.25	2.00	4.25	4	7/8	9	1.00	1.44	18	8.5	
1 1/4	2.25	7.25	2.50	5.12	4	1	8	1.12	1.56	27	11	
1 1/2	2.50	8.00	2.88	5.75	4	1 1/8	8	1.25	1.81	35	14	
2	2.25	9.25	3.62	6.75	8	1	8	1.12	1.56	43	18	
2 1/2	2.50	10.50	4.12	7.75	8	1 1/8	8	1.25	1.81	59	23	
3	2.75	12.00	5.00	9.00	8	1 1/4	8	1.44	2.12	84	30	
4	3.25	14.00	6.19	10.75	8	1 1/2	8	1.69	2.38	127	40	
5	3.75	16.50	7.31	12.75	8	1 3/4	8	2.00	2.81	199	55	
6	4.12	19.00	8.50	14.50	8	2	8	2.25	3.31	291	72	
8	4.38	21.75	10.62	17.25	12	2	8	2.25	3.31	361	91	
10	5.12	26.50	12.75	21.25	12	2 1/2	8	2.81	4.00	640	134	
12	5.50	30.00	15.00	24.38	12	2 3/4	8	3.12	4.38	873	168	